

Subwoofer 218S			
HP Resp (Type,dB/Oct)	BW24dB	LP Resp (Type,dB/Oct)	LR24
HP Frequency (Hz)	40	LP Frequency (Hz)	90
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	2.5ms		
Filter Type	PEQ 1		
Freq. (Hz)	132		
Octave Bandwidth	0.33		
Level (dB)	-8		
1596 LF			
HP Resp (Type,dB/Oct)	LR24	LP Resp (Type,dB/Oct)	BU12
HP Frequency (Hz)	80	LP Frequency (Hz)	1.5Khz
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Filter Type	PEQ 1	PEQ 2	
Freq. (Hz)	650	1300	
Octave Bandwidth	0.44	0.33	
Level (dB)	-5	6	
1596 HF			
HP Resp (Type,dB/Oct)	LR24		
HP Frequency (Hz)	1.7K		
HP Polarity (Norm/Inv)	Norm		
Filter Type	PEQ 1	PEQ 2	
Freq. (Hz)	5000	12000	
Octave Bandwidth	0.5	0.5	
Level (dB)	-4.5	-3	

Subwoofer 218S			
HP Resp (Type,dB/Oct)	BW24dB	LP Resp (Type,dB/Oct)	LR24
HP Frequency (Hz)	40	LP Frequency (Hz)	90
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	2.5ms		
Filter Type	PEQ 1		
Freq. (Hz)	132		
Octave Bandwidth	0.33		
Level (dB)	-8		
3294 LF			
HP Resp (Type,dB/Oct)	BU24	LP Resp (Type,dB/Oct)	BU18
HP Frequency (Hz)	100	LP Frequency (Hz)	570
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	271 ms		
Filter Type	PEQ 1	PEQ 2	
Freq. (Hz)	440	226	
Octave Bandwidth	0.6	0.33	
Level (dB)	-2.5	-4	

3294 HF

HP Resp (Type,dB/Oct) BU24
HP Frequency (Hz) 652
HP Polarity (Norm/Inv) Norm
Level -2

Filter Type	PEQ 1	PEQ 2	PEQ 3	PEQ 4	PEQ 5
Freq. (Hz)	870	1581	1185	2111	4383
Octave Bandwidth	0.33	0.2	0.28	0.38	0.2
Level (dB)	2	-3	-6	5	-2.5

Subwoofer 215S

HP Resp (Type,dB/Oct)	BW24dB	LP Resp (Type,dB/Oct)	LR24
HP Frequency (Hz)	40	LP Frequency (Hz)	90
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	2.5ms		

Filter Type	PEQ 1	PEQ 2
Freq. (Hz)	132	64
Octave Bandwidth	0.33	0.19
Level (dB)	-8	-6

3594 LF

HP Resp (Type,dB/Oct)	BU24	LP Resp (Type,dB/Oct)	BU18
HP Frequency (Hz)	100	LP Frequency (Hz)	570
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	.271 ms		

Filter Type	PEQ 1	PEQ 2	PEQ 3
Freq. (Hz)	126	226	419
Octave Bandwidth	0.33	0.33	0.33
Level (dB)	-2	-4	-4

3594 HF

HP Resp (Type,dB/Oct)	BU24
HP Frequency (Hz)	652
HP Polarity (Norm/Inv)	Norm

Filter Type	PEQ 1	PEQ 2	PEQ 3	PEQ 4	PEQ 5
Freq. (Hz)	1325	2000	2800	4380	8500
Octave Bandwidth	0.28	0.22	0.4	0.2	0.33
Level (dB)	-7	4	3	-2	-5

Subwoofer 218S

HP Resp (Type,dB/Oct)	BW24dB	LP Resp (Type,dB/Oct)	LR24
HP Frequency (Hz)	40	LP Frequency (Hz)	90
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	2.5ms		

Filter Type	PEQ 1
Freq. (Hz)	132
Octave Bandwidth	0.33
Level (dB)	-8

3594 LF

HP Resp (Type,dB/Oct)	BU24	LP Resp (Type,dB/Oct)	BU18
HP Frequency (Hz)	100	LP Frequency (Hz)	570
HP Polarity (Norm/Inv)	Norm	LP Polarity (Norm/Inv)	Norm
Delay	.271 ms		

Filter Type	PEQ 1	PEQ 2	PEQ 3
Freq. (Hz)	126	226	419
Octave Bandwidth	0.33	0.33	0.33
Level (dB)	-2	-4	-4

3594 HF

HP Resp (Type,dB/Oct) BU24
HP Frequency (Hz) 652
HP Polarity (Norm/Inv) Norm

Filter Type	PEQ 1	PEQ 2	PEQ 3	PEQ 4	PEQ 5
Freq. (Hz)	1325	2000	2800	4380	8500
Octave Bandwidth	0.28	0.22	0.4	0.2	0.33
Level (dB)	-7	4	3	-2	-5