

**WET**

Model	322-64		322-94		315-64	
Frequency Band	LO	HI	LO	HI	LO	HI
Connector	OUT 1	OUT 2	OUT 1	OUT 2	OUT 1	OUT 2
Input Source Routing	1	1	1	1	1	1
Filter 1 Type	PEQ	PEQ	PEQ	PEQ	PEQ	PEQ
Filter 1 Freq. (Hz)	432	3422	432	5900	313	2.5K
Filter 1 (Oct/BW)	0.6	0.3	0.6	0.32	0.33	0.2
Filter 1 Level (dB)	-3.5	-4	-3.5	-2	3	2
Filter 2 Type	PEQ	PEQ	PEQ	PEQ	PEQ	PEQ
Filter 2 Freq. (Hz)	242	1720	242	1940	435	3.6K
Filter 2 (Oct/BW)	0.2	0.38	0.2	0.21	0.23	0.2
Filter 2 Level (dB)	2.5	3	2.5	3	-7	-2.5
Filter 3 Type	PEQ	PEQ	PEQ	PEQ		PEQ
Filter 3 Freq. (Hz)	840	5420	840	3800		4.7
Filter 3 (Oct/BW)	0.16	0.4	0.16	0.32		0.49
Filter 3 Level (dB)	-15	2	-15	2		-6
Filter 4 Type		PEQ		PEQ		PEQ
Filter 4 Freq. (Hz)		8420		7100		1330
Filter 4 (Oct/BW)		-2		2.5		0.44
Filter 4 Level (dB)		0.3		0.3		-3
HP Resp (Type,dB/Oct)	BW24dB	LR24	BW24dB	LR24	LR24dB	BW12dB
HP Frequency (Hz)	60	800	60	600	60	800
HP Polarity (Norm/Inv)	Norm	Norm	Norm	Norm	Norm	Norm
LP Resp (Type,dB/Oct)	BW12dB		BE24		BW12dB	
LP Frequency (Hz)	800		500		800	
LP Polarity (Norm/Inv)	Norm		Norm		Norm	
Input Delays (mSec)	.62 ms		0.45ms		0.458ms	
Output	0	-1.5	0	0	0	-10